

STEINEL Lighting Controls

STEINEL, a leading manufacturer of award-winning lighting controls from Germany, brings a new and innovative line of controls to North America.

For specifiers, distributors, contractors or facility managers looking for superior lighting control, these products bring you a new level of quality, performance, and energy savings.

Customer Service Call (800) 852-4343

For Technical Support & Design Layout Call (888) 298-8298



www.steinel.net

M-21004-1

STEINEL[®]
PROFESSIONAL

STEINEL Lighting Controls

Setting the Standard in Presence Detection



STEINEL[®]
PROFESSIONAL

Image	Model	Part #	Technology	Switching Zones	Mounting	Coverage	Voltage	Options	
Control Pro Presence Detectors									
	IR Quattro HD COM1-24	64460	HD PIR	4800	Ceiling	360° Square Scalable Presence: 26 x 26 ft Radial: 26 x 26 ft Tangential: 65 x 65 ft	18-24 VDC/VAC	NO/NC Contact	
	IR Quattro HD COM2-24	64470						1-10 V Dimming	
	IR Quattro HD DIM-24	64480							
	IR Quattro HD COM1-WR	64490						120/277 VAC	
	IR Quattro HD KNX	64500						24 V via KNX bus	KNX
	IR Quattro COM1-24	64410	PIR	1760	Ceiling	360° Square Scalable Presence: 15 x 15 ft Radial: 15 x 15 ft Tangential: 23 x 23 ft	18-24 VDC/VAC	NO/NC Contact	
	IR Quattro COM2-24	64420						1-10 V Dimming	
	IR Quattro DIM-24	64430							
	IR Quattro COM1-WR	64440						120/277 VAC	
	IR Quattro KNX	64450						24 V via KNX bus	KNX
	DT Quattro COM1-24	64700	PIR & 40 kHz Ultrasonic	520	Ceiling	360° Presence: 20 x 20 ft Radial: 32 x 32 ft Tangential: 32 x 32 ft	18-24 VDC/VAC	NO/NC Contact	
	DT Quattro COM2-24	64710						1-10 V Dimming	
	DT Quattro DIM-24	64720							
	US Quattro COM1-24	64510	40 kHz Ultrasonic		Ceiling	360° Presence: 20 x 20 ft Radial: 32 x 32 ft Tangential: 32 x 32 ft	18-24 VDC/VAC	NO/NC Contact	
	US Quattro COM2-24	64520						1-10 V Dimming	
	US Quattro DIM-24	64530							
	US Hallway COM1-24	64550	40 kHz Ultrasonic		Ceiling	Hallway 6.5 x 65 ft Max	18-24 VDC/VAC	NO/NC Contact	
	US Hallway COM2-24	64560						1-10 V Dimming	
	US Hallway DIM-24	64570							
	US Oneway COM1-24	64600	40 kHz Ultrasonic		Ceiling	180° 6.5 x 33 ft Max	18-24 VDC/VAC	NO/NC Contact	
	US Oneway COM2-24	64610						1-10 V Dimming	
	US Oneway DIM-24	64620							
	IR CM COM1-24	65400	PIR	520	Ceiling & Wall	160° Presence: 22 ft Radial: Max. 26 ft Tangential: Max 82 ft	18-24 VDC/VAC	NO/NC Contact	
	IR CM COM2-24	65420						1-10 V Dimming	
	IR CM DIM-24	65440							
	DT CM COM1-24	65500	PIR & 40 kHz Ultrasonic	520	Ceiling & Wall	160° Presence: 22 ft Radial: Max. 38 ft Tangential: Max 82 ft	18-24 VDC/VAC	NO/NC Contact	
	DT CM COM2-24	65520						1-10 V Dimming	
	DT CM DIM-24	65540							
Control Pro Accessories									
	Smart Remote	65900	Smart App Commissioning Remote						
	RC 3	65300	Programming Remote for Control Pro Series						
	RC 4	65320	User Remote for Control Pro Series						
	RC 6 KNX	65600	Programming Remote for Control Pro Series KNX Network Communication Protocol Detectors						
	RC 7 KNX	65700	User Remote for Control Pro Series KNX Network Communication Protocol Detectors						
	RC 8	65800	Programming Remote with Basic Light Level Settings for Control Pro Series						
	WGC	65330	Wire Guard Cage						
	Power Packs								
	TR 100	63101	Manual/Auto (ON)		J - Box		120/277 VAC	NO/NC Contact	
	TR 150	63205							
	TR 100-A	63103	Auto (ON)		J - Box		120/277 VAC	NO/NC Contact	
	TR 150-A	63207							
	TR 100-M	63102	Manual (ON)		J - Box		120/277 VAC	NO/NC Contact	
	TR 150-M	63206							

Image	Model	Part #	Technology	Switching Zones	Buttons	Mounting	Coverage	Voltage	IP Class			
IS Series Occupancy Sensors												
	IS 3360-24	61133	PIR	1416		Ceiling	360° 12.5 ft Radial / 65 ft Tangential	24 VDC	IP20			
	IS 3180-24	61131								448	Wall	180° 12.5 ft Radial / 65 ft Tangential
	IS 345-24	61134								280	Ceiling	13 x 40 ft Linear Reach
	IS D360-24	61136								720	Ceiling	360° 13 ft Radial / 26 ft Tangential
IS Series Accessories												
	ISDC-B	61141	IS 3360-24, IS 3180-24 & IS 345-24 Design Cover, Black									
	ISDC-I	61142	IS 3360-24, IS 3180-24 & IS 345-24 Design Cover, Inox									
	CWB-B	61143	IS 3180-24 Corner Mounting Bracket, Black									
	CWB-W	61144	IS 3180-24 Corner Mounting Bracket, White									
Wall Switch Occupancy Sensors												
	IR WLS 1-W (White)	66100	PIR	96	1	Wall Switch	180° Minor Motion: 21 x 18 ft Radial: 24 ft (904 sq.ft.) Tangential: Max. 54 ft (4,500 sq.ft.)	120/277 VAC	IP20			
	IR WLS 1-LA (Lt Almond)	66110										
	IR WLS 2-W (White)	66130	PIR	96	2	Wall Switch	180° Minor Motion: 21 x 18 ft Radial: 24 ft (904 sq.ft.) Tangential: Max. 54 ft (4,500 sq.ft.)	120/277 VAC	IP20			
	IR WLS 2-LA (Lt Almond)	66140										
	US WLS 1-W (White)	66160	40 kHz Ultrasonic		1	Wall Switch	180° Minor Motion: 18 x 12 ft Radial: 24 ft (904 sq.ft.) Tangential: Max. 24 ft (904 sq.ft.)	120/277 VAC	IP20			
	US WLS 1-LA (Lt Almond)	66170										
	US WLS 2-W (White)	66190	40 kHz Ultrasonic		2	Wall Switch	180° Minor Motion: 18 x 12 ft Radial: 24 ft (904 sq.ft.) Tangential: Max. 24 ft (904 sq.ft.)	120/277 VAC	IP20			
	US WLS 2-LA (Lt Almond)	66200										
	DT WLS 1-W (White)	66220	PIR & 40 kHz Ultrasonic	96	1	Wall Switch	180° Minor Motion: 21 x 18 ft Radial: 24 ft (904 sq.ft.) Tangential: Max. 54 ft (4,500 sq.ft.)	120/277 VAC	IP20			
	DT WLS 1-LA (Lt Almond)	66230										
	DT WLS 2-W (White)	66250	PIR & 40 kHz Ultrasonic	96	2	Wall Switch	180° Minor Motion: 21 x 18 ft Radial: 24 ft (904 sq.ft.) Tangential: Max. 54 ft (4,500 sq.ft.)	120/277 VAC	IP20			
	DT WLS 2-LA (Lt Almond)	66260										
Fixture Integrated												
	HFLUM2-WR	65122	5.8 GHz			Fixture Mount	360° adj. 3.3 to 26 ft Reach	120/277 VAC				
High Bay Sensors												
	HBS 300 (Bulk P)	64130	PIR	1416		Fixture or J - Box	360° Radial Reach: 22 ft Tangential Reach: 60 ft	120/277 VAC	IP20			
	HBS 300	64131										
	HBS 200 (Bulk P)	64120	PIR	104		Fixture or J - Box	Aisle Linear Detection: 100 x 13 ft	347/480 VAC	IP20			
	HBS 200	64121										
	HBS 300 (347-480V) (Bulk P)	64132	PIR	1416		Fixture or J - Box	360° Radial Reach: 22 ft Tangential Reach: 60 ft	347/480 VAC	IP20			
	HBS 300 (347-480V)	64133										
	HBS 200 (347-480V) (Bulk P)	64122	PIR	104		Fixture or J - Box	Aisle Linear Detection: 100 x 13 ft	120/277 VAC	IP65			
	HBS 200 (347-480V)	64123										
	HBS 300-WL	64134	PIR	1416		Fixture or J - Box	360° 22 ft Radial / 60 ft Tang.	120/277 VAC	IP65			
	HBS 200-WL	64124								104	Aisle Linear Det.: 100 x 13 ft	
High Bay Sensor Accessories												
	LC 1	64301	Aisle Starter Lens Cover for HBS 200									
	LC 4	64304	Reduced Range Lens Cover for HBS 300									
	LC 5	64305	180° Lens Cover for HBS 300									
	EM 1	64307	High Bay Extension Module									
Outdoor Sensors												
	IS 360W (White)	60261	PIR	720		Ceiling	360° 40 ft Reach	120 VAC	IP54			
	IS 360B (Black)	60251										
	IS 240-120W (White)	61621	PIR	304		Wall	240° 40 ft Reach	120 VAC	IP54			
	IS 240-120B (Black)	61622										